



Accessories

Digital Thermometer & Data Logger

Model	Description
<p>HTC-2 Digital Thermometer & Hygrometer</p> 	<p>Function and features:</p> <ul style="list-style-type: none"> ❖ Display Indoor and outdoor temperature simultaneously ❖ Switch between C/F ❖ Max./Min. temperature value memory ❖ Max./Min. temperature value recovery function ❖ Dimension: H110mm xL100mm
<p>TempU-03 Temperature & Humidity USB Data Logger</p> 	<p>Function and features:</p> <ul style="list-style-type: none"> ❖ Display refrigerator temperature (internal) ❖ Startup mode use button or software ❖ Humidity sensor calibration off set function ❖ 3.6V Lithium (Lasts approximately 1 year) ❖ Temperature range -30°C to +60°C ❖ Can print the data logger report. ❖ Comes with Certificate of Calibration ISO 17025 ❖ Dimension W x D x H: 89mm x 36mm x 16mm
<p>TempU-04 Temperature & Humidity USB Data Logger</p> 	<p>Function and features:</p> <ul style="list-style-type: none"> ❖ Display refrigerator temperature (internal) ❖ Startup mode use button or software ❖ Humidity sensor calibration off set function ❖ CR2032 3.0V Lithium Battery ❖ Temperature range -30°C to +60°C ❖ Printable the data logger report. ❖ Accompany with Certificate of Calibration ISO 17025 ❖ Dimension W x D x H: 89mm x 36mm x 16mm
<p>TempU-06 L60 Temperature & Humidity USB Data Logger</p> 	<p>Function and features:</p> <ul style="list-style-type: none"> ❖ Display refrigerator temperature (external temperature sensor) ❖ Start mode: Push to start or Timing start. ❖ Display large LCD Screen with powerful indicators ❖ Log Interval : Programmable (10s-18h) (Default:10 mins) ❖ Temperature range -60°C to + 120°C ❖ Generate report PDF/CSV Report automatically. ❖ Connectivity USB 2.0 Bluetooth 4.2 ❖ Accompany with Certificate of Calibration ISO 17025 ❖ Dimension W x D x H: 115mm x 50mm x 20mm
<p>TempU-06 L60 100 Temperature & Humidity USB Data Logger</p> 	<p>Function and features:</p> <ul style="list-style-type: none"> ❖ Display refrigerator temperature (external temperature sensor) ❖ Start mode: Push to start or Timing start. ❖ Display large LCD Screen with powerful indicators ❖ Log Interval : Programmable (10s-18h) (Default:10 mins) ❖ Temperature range -100°C to + 80°C with accuracy ±0.5°C. ❖ Generate report PDF/CSV Report automatically. ❖ Connectivity USB 2.0 Bluetooth 4.2 ❖ Accompany with Certificate of Calibration ISO 17025 ❖ Dimension W x D x H: 115mm x 50mm x 20mm
<p>DSM 9000 SMS Alarm System (Main unit only)</p> 	<p>Function and features:</p> <ul style="list-style-type: none"> ❖ Able to send SMS max 5 telephone numbers, during power failure or high/low temperature alarm alert is triggered. ❖ Max link-up 2 units freezer(s)/refrigerator(s) ❖ With remote alarm contact, external audio & visual alarm. ❖ DC Backup battery last for 72 hours.