



Industrial Refrigerators

+2°C to +8°C (E Series) | Single door

ETS Industrial Refrigerators and freezers are designed and fabricated to meet the demanding requirements of industrial applications. These refrigerators and freezers provide complete and integrated solutions for pharmaceuticals, food, seafood, bakeries, restaurants, supermarkets, warehouses and reagents, etc. Suitable for research centers, factories/companies, etc. Wide ranges of models are offered to accommodate your needs and requirements.

Features:

- ✓ Use User-friendly design
- ✓ Precise microcomputer temperature control
- ✓ Standard alarms and safety features
- ✓ Forced-air circulation for enhanced temperature stability
- ✓ Easy-to-read LED temperature display
- ✓ Visual and audible alarm alerts
- ✓ Low-noise compressor-friendly design
- ✓ Low-noise compressor



VC 70E-C



VC 200 E-C



VC 300E-C



VC 500E-C/ 600E-C/
700E-C/ 800E-C

Model	VC 70E-C	VC 200E-C	VC 300E-C	VC 500E-C	VC 600E-C	VC 700E-C	VC 800E-C
Dim. Ext (mm) W x D x H	580 x 500 x 900	595 x 605 x 1620	600 x 610 x 1945	640 X 800 X 2070	700 x 800 x 2070	800 x 800 x 2070	800 x 810 x 2245
Dim. Int. (mm) W x D x H	360 x 410 x 510	515 x 510 x 1085	510 x 410 x 1370	540 X 650 X 1430	600 x 600 x 1510	710 x 660 x 1510	710 x 670 x 1670
Capacity	70L	200L	300L	500L	600L	700L	800L
Internal Chamber	Stainless Steel		Stainless Steel 304	Epoxy Powder Coated			
External Chamber	Epoxy Powder Coated Mild Steel						
Shelves (hold 50kg)	3 nos.	3 nos.	4 nos.	5 nos.	5 nos.	5 nos.	5 nos.
Temp. Controller	Temp adjustable, LED display						
Temp Fluctuation	±1.0°C						
Internal Air Circulation	Forced-air						
Refrigerant	R134a CFC Free						
Glass Door	1 no. Heated Glass Door						
Door Lock / Castor	1 no. / 4 nos.	1 no. / 4 nos.	1 no. / 4 nos.	1 no. / 4 nos.	1 no. / 4 nos.	1 no. / 4 nos.	1 no. / 4 nos.
Comp. Recip. Hermetic	200W	200W	200W	250W	400W	400W	400W
Power Voltage	230Vac 50Hz Single Phase (60Hz for others)						
Standard LED Alarm System							
- Hi/Low Alarm	√	√	√	√	√	√	√
- Remote Alarm Contact	√	√	√	√	√	√	√
- Power Failure		√	√	√	√	√	√
- 72-hour DC backup		√	√	√	√	√	√
* Accessories (Optional)	Door Fan Switch						
Safety Features & Certification	ISO 13485, Electric Safety Test (EST) IEC 61010-1 (2010), GDPMD, ISO IEC 17025						