



Industrial Refrigerators

+2°C to +8°C (*E Series*) | 2-door & 3-door



VC 1050E-C/ 1200E-C/ 1400E-C



VC 1600E-C/ 1800E-3C/ 2400E-3C

Model	VC 1050- C	V 1200E-C	V 1400-C	VC 1600-C	V1800E-3 C	VC 2400E-3 C
Dim. Ext. (mm) W x D x H	1260 x 800 x 2070	1440 x 800 x 2070	1540 x 850 x 2070	1630 x 790 x 2245	2200 x 800 x 2080	2360 x 813 x 2400
Dim. Int. (mm) W x D x H	1150 x 650 x 1430	1315 x 650 x 1430	1390 x 710 x 1440	1485 x 720 x 1670	2050 x 710 x 1430	2050 x 660 x 1430
Capacity	1,050L	1,200L	1,400L	1,800L	1,600L	2,400L
Int. & Ext. Chamber	Epoxy powder coated					
Temp. Controller	Temp adjustable, LED display					
Temp Fluctuation	±1.0°C					
Internal Air Circulation	Forced-air					
Refrigerant	R134a CFC Free					
Glass Door	Heated Glass Double Door				Heated Glass 3-Door	
No. of Shelves	10 pcs	10 pcs	10 pcs	10 pcs	15 pcs	15 pcs
Light	1pc	1pc	1pc	1pc	2 pcs	2 pcs
Door Lock / Castor	2 nos./4 nos.	2 nos./4 nos.	2 nos./4 nos.	2 nos./4 nos.	3 nos./4 nos.	3 nos./4 nos.
Comp. Recip. Hermetic	1/3 HP	3/4 HP	3/4 HP	3/4 HP	3/4 HP	3/4 HP
Power Voltage	230Vac 50Hz Single Phase (60Hz for others)					
Standard LED Alarm System						
- Hi/Low Alarm	√	√	√	√	√	√
- Remote Alarm Contact	√	√	√	√	√	√
- Power Failure	√	√	√	√	√	√
- 72-hour DC backup	√	√	√	√	√	√
Accessories (Optional)	LCD Digital Display, USB Data Logger, Drawer(s), Chart Recorder, Fan door switch					
Safety Features & Certification	ISO 13485, Electric Safety Test (EST) IEC 61010-1 (2010), GDPMD, ISO IEC 7025					