



Low Temperature Upright Freezer

0°C to -25°C (Manual Defrost)

Our Low Temperature Upright Freezers are designed and manufactured to provide reliable, frozen environments as low as -25°C to ensure safe storage of various type of foods. Units are complete with digital temperature touch screen display, standard LED alarm system, inner doors for added security, and swivel castors.

Features:

- ✓ User-friendly design and easy-to-manage layout
- ✓ Precise microcomputer temperature control
- ✓ Direct cooling with Manual Defrost
- ✓ Easy-to-read LED temperature display
- ✓ Visual and audible alarm alerts
- ✓ Low-noise compressor
- ✓ Large temperature ranges for storing goods: from 0°C to -25°C
- ✓ Precise microcomputer temperature control
- ✓ Standard alarms and safety features
- ✓ Forced-air circulation for enhanced temperature stability
- ✓ Easy-to-read LED temperature display
- ✓ Visual and audible alarm alerts
- ✓ Low-noise compressor



VF 25U-100(M)-C / 280(M)-C



VF 25U-500(M)-C / 600(M)-C / 700(M)-C / 800(M)-C

Model	VF 25U-100(M)-C	VF 25U-280(M)-C	VF 25U-500(M)-C	VF 25U-600(M)-C	VF 25U-700(M)-C	VF 25U-800(M)-C
Dim. Ext (mm) W x D x H	720 x 735 x 1260	810 x 730 x 1600	800 x 720 x 1840	940 x 900 x 1900	940 x 950 x 1920	1090 x 980 x 1860
Dim. Int. (mm) W x D x H	460 x 460 x 510	630 x 676 x 855	640 x 450 x 1400	760 x 695 x 1180	760 x 740 x 1285	910 x 775 x 1200
Capacity	100L	280L	500L	630L	730L	860L
Internal Chamber	Stainless Steel 304					
External Chamber	Epoxy Coated Mild Steel White Color					
Temp. Controller	LED Digital Microprocessor					
Door Lock	1 no.	1 no.	1 no.	1 no.	1 no.	1 no.
Castor	4 nos.	4 nos.	4 nos.	4 nos.	4 nos.	4 nos.
Internal Air Circulation	Direct Cooling					
Refrigerant	R404a CFC Free					
No. of Shelf(s)	2 nos.	5 nos.	5 nos.	5 nos.	5 nos.	5 nos.
Insulation Foaming	60mm	60mm	60mm	60mm	60mm	60mm
Power Voltage	240Vac 50Hz Single Phase (60Hz for others)					
Standard LED Alarm System						
- Hi/Low Alarm	√	√	√	√	√	√
- Power Failure	√	√	√	√	√	√
- Low Battery	√	√	√	√	√	√
- Door Ajar	√	√	√	√	√	√
- Dirty Condenser	√	√	√	√	√	√
Safety Features & Certification	ISO 13485, Electric Safety Test (EST) IEC 61010-1 (2010), GDPMD,SO IEC 17025					

- **NOTE : VC 25U-280(F) WITH MDA CLASS A CERTIFICATE**
- **Capacity may vary according to the loading preferences and contents. Can be customized**