



Low Temperature Upright Freezer (*Force Air*)

0°C to -25°C (*Auto Defrost*)

Our Low Temperature Upright Freezers are designed and fabricated to provide reliable, frozen environments as low as -25°C to ensure safe storage of various type of foods. Unit sizes vary from 500L to 1,500L and complete with standard LED alarm system, door locks, heated glass door(s) and swivel castors.

Features:

- ✓ User-friendly design and easy-to-manage layout.
- ✓ Precise microcomputer temperature control
- ✓ Auto-defrost
- ✓ Forced-air circulation to enhanced temperature stability
- ✓ Easy-to-read LED temperature display
- ✓ Visual and audible alarm alerts
- ✓ Low-noise compressor
- ✓ Large temperature ranges for storing goods: from 0°C to -25°C
- ✓ Low-noise compressor



VF 25U-500(G)-C



VF 25U-1000(G)-C



VF 25U-1500(G)-C

Model	VF 25U-500(G)-C	VF 25U-1000(G)-C	VF 25U-1500(G)-C
Dim. Ext (mm) W x D x H	640 x 800 x 2070	1260 x 800 x 2070	1260 x 800 x 2070
Dim. Int. (mm) W x D x H	540 x 650 x 1430	1100 x 650 x 1430	1100 x 650 x 1430
Capacity	500L	1000L	1500L
Int. & Ext. Chamber	Epoxy Coated Mild Steel	Epoxy Coated Mild Steel	Epoxy Coated Mild Steel
Temp. Controller	Temp adjustable, LED display		
Internal Air Circulation	Forced Air		
Refrigerant	R404a CFC Free		
Door	Heated Glass Door		
No. of Shelf(s)	4 nos.	8 nos.	12 nos.
Door Lock / Castor	1 no / 4 nos.	2 nos./4 nos.	3 nos./4 nos.
Comp. Recip. Hermetic	550W	550W	650W
Power Voltage	240Vac 50Hz Single Phase (60Hz for others)		
Standard LED Alarm System			
- Hi/Low Alarm	✓	✓	✓
- Delay Start Up	✓	✓	✓
- Auto Defrost	✓	✓	✓
- Accessories (Optional)	Door Fan Switch		
Safety Features & Certification	ISO 13485, Electric Safety Test (EST) IEC 61010-1 (2010), GDPMD, SO IEC 17025		

- **NOTE : WITH MDA CLASS A CERTIFICATE (MODEL:VC)**
- **Capacity may vary according to the loading preferences and contents. Can be customized**